



FloodMaster® RS-0xx Wired Leak Detection System Accessories



Wired Water Sensors


Additional wired sensors are compatible with most FloodMaster RS-0xx series units. Up to 5 additional sensors can be paired with an existing receiver box. Units have plenum-rated wire and ship with flying leads.

The sensor features a 1/16" stand-off to allow for air circulation and eliminate false alarms caused by humidity from the floor. The detection level is the same in either vertical or horizontal sensor orientation to the floor – making it ideal for tight or hard-to-reach spaces.


The sensor housing has embedded magnets which adhere to the provided metal plate or other metal surface in the desired installation location. It also provides a through hole which allows the sensor to be screwed in place for a more tamper-resistant installation.

Wired Sensors

Cable Length	P/N	UPC
8'	RSA-101-008	811475030214
25'	RSA-101-025	811475030221
50'	RSA-101-050	811475030238
100'	RSA-101-100	811475030245



HORIZONTAL
INSTALL OPTIONS
VERTICAL



Sensing Rope Accessory Kit

This rope-style water sensor can be used in place of traditional sensors to provide a wider area of leak detection, or to monitor low tanks, room perimeters, sub-floors, etc.

This highly absorbent water sensing rope is constructed from two twisted metal conductor wires that are insulated from one another and surrounded by a polyethylene mesh braid jacket. The ends are male/female quick-disconnect snap connectors for easy installation and removal. Up to 100 feet of sensor rope (10 lengths) may be connected to a single receiver box.

Sensing Rope

Description	P/N	UPC
10' Sensing Rope Kit	RSA-175-810	857640005557
Add-On 10' Rope Length	RSA-175-010	857640005540

RSA-175-810 kit includes:

- (1) Lead Wire (6')
- (1) Sensing Rope (10')
- (2) Hold Down Accessories



Auto Dialer

A convenient, low-cost add-on to send and receive automatic phone alerts whenever your system identifies a fault condition. Triggers calls with a recorded message to up to nine telephone numbers.

Requires a dedicated analog phone line.

P/N	UPC
RSA-600-003	857640005670



Cable Adder

Cable extension that allows for easy remote mounting of the RS-080 receiver box further away from the valve.

Length	P/N	UPC
10'	RSA-400-010	857640005595
25'	RSA-400-025	857640005601
50'	RSA-400-050	857640005618
100'	RSA-400-100	857640005625



Electrical Plug Interrupter

This power control relay for conventional plug-in Power-Vent gas water heaters automatically turns off the electricity to the appliance when a leak is detected by an RS-094 system.

Certified to CAN/CSA-C22.2 No. 61010-1-12: Safety Requirements for Electrical Equipment for Measurement, Control and Laboratory use – Part 1: General Requirements.

P/N	UPC
RSA-600-001	857640005656



Reliance Detection Technologies, LLC
27 Business Park Drive, Branford, CT 06405

RelianceDetection.com 888-771-4929

• Tel: 203-488-2684 • Fax: 203-481-5036 • info@RelianceDetection.com