

Battery Operated Water Heater Leak Detection & Automatic Water Shut-Off System

Damage caused by indoor plumbing leaks can not only cost thousands in repairs, but can also result in:

- Loss of property and equipment
- Thousands of gallons of wasted water
- Massive disruption to homeowners and tenants
- Increased insurance premiums and possible reduced coverage

Description:

The RS-074-3/4 has been designed to protect your home against water leaks caused by the water heater. The RS-074-3/4 is a battery-operated shut-off unit installed on the cold water pipe feeding the water heater. The valve closes automatically when the sensor detects leaking water.

Function:

The RS-074-3/4 can be installed in any orientation. Valve installation is non-directional with female 3/4 NPT thread on both ends. It has a Water Sensor connected to the Actuator/Valve with a 10 ft. long lead wire. The Sensor is installed at the base of the tank in the pan or on the floor near the tank. The RS-074-3/4 is battery operated so no plug or outlet is required. And the unit is NOT affected by power outages. 4 year battery life.

Specifications:

- NSF/ANSI 372 Certified, Full Port, Lead Free Valve
- 3/4 NPT Thread
- (2) CR123 Lithium Batteries (included with kit)
- Batteries: Operating Voltage – 3V
- Water Sensor Cable Length – 10 ft.
- Cable Standard: ISO9001
- Operating Temperature: 32°F / 122°F
- Dimensions: 5.5" L x 2.95" W x 4.33" H
- Weight: 26.1 oz.



Features:

- Valve: Twice monthly automatic self-cleaning cycle
- Manual Re-set by turning lever handle
- Two year limited warranty
- Low battery alert

For further information, refer to Reliancedetection.com for:

- RS-074-3/4 Installation Instructions
- Other resources such as how to buy